

# BARRIER WASHER EXTRACTORS

## WITH STATE-OF-THE-ART FEATURES

### Features

### LCA-50 T

- High spin soft mounted washer extractor, no need of anchorage, 2 opposed doors.
- Extraction speed 945 RPM.
- G force 400.
- Horizontally suspended drum by means of 2 axes which increase robustness, 1 compartment.
- Electric or steam heating.
- New EASY TOUCH microprocessor with Touch Screen and a lot of devices for a greater flexibility.
- 26 preset programs, unlimited creation of new programs.
- WET CLEANING system integrated (standard).
- Standard double display.
- OPTIMAL LOAD system integrated: manual indication of the load.
- 3 water inlets standard.
- Capacity 49 kg.
- Body, drum and vat in stainless steel.
- Soap dispenser with 4 compartments.
- 8 signals for dosing pumps.
- Out of balance detection by means of the inverter.
- Traceability- data storage integrated.



Emissions CO<sub>2</sub>/carbon footprint



Energy efficiency



Minimum consumption of water



Low chemical consumption



Touch technology



Stainless steel



Automatic mixer (hot/cold water)



Inverter



Wet cleaning



Optimal KG



Easy maintenance



Third water inlet

### Options

- 2nd drain valve.
- Central position of drain valve.
- Titration valve.
- Automatic weighing sensor system on feet.
- Drum electric brake.
- Relay card to increase up to 14 signals for dosing pumps.
- Plinth up to 850 mm loading height from door bottom.
- Stainless steel wall frame with rubber.
- Lighting column at the end of cycle.
- Dual heating electric- steam.



Automatic weighing system (optional)